



LED DOWN LIGHT SERIES



CGD-LD205(Round)

CGD-LD205(Square)



Specifications

Input Voltage	Non-Dimmable	AC100-240V 50/60HZ; AC200-240V 50/60HZ	
	Dimmable	AC100-120V 50/60HZ; AC200-240V 50/60HZ	
LED Current	Constant Current 350mA		
Light Source	4014 SMD LED		
Power	11W ± 10% / 15W ± 10% (LD205 Round) 15W ± 10% / 18W ± 10% (LD205 Square)		
CCT	3000K/4000K/6000K		
Beam Angle	90°		
Operation Temperature	-20°C+50°C		
Lamp working temperature	≤ 60°C		
Life Span	50000Hours		
CRI	>80		
Luminous Flux	11W ± 10% (LD205 Round)	3000K	815 lm ± 5%
		4000K	965 lm ± 5%
		6000K	990 lm ± 5%
	15W ± 10% (LD205 Round)	3000K	1200 lm ± 5%
		4000K	1315 lm ± 5%
		6000K	1350 lm ± 5%
	15W ± 10% (LD205 Square)	3000K	1215 lm ± 5%
		4000K	1360 lm ± 5%
		6000K	1375 lm ± 5%
	18W ± 10% (LD205 Square)	3000K	1400 lm ± 5%
		4000K	1445 lm ± 5%
		6000K	1495 lm ± 5%
Surface color	White		

Lumens data depends on LED brand, beam angle All information is subject to our final conformation.
Welcome to contact us and ask for IES files.