



LED DOWN LIGHT SERIES



CGD-LD206(Round)



CGD-LD206(Square)



Specifications

Input Voltage	Non-Dimmable	AC100-240V 50/60HZ; AC200-240V 50/60HZ	
	Dimmable	AC100-120V 50/60HZ; AC200-240V 50/60HZ	
LED Current	Constant Current 350mA		
Light Source	4014 SMD LED		
Power	15W ± 10% / 18W ± 10% (LD206 Round) 15W ± 10% / 18W ± 10% (LD206 Square)		
CCT	3000K/4000K/6000K		
Beam Angle	90°		
Operation Temperature	-20°C-+50°C		
Lamp working temperature	≤ 60°C		
Life Span	50000Hours		
CRI	>80		
Luminous Flux	15W ± 10% (LD206 Round)	3000K	1205 lm ± 5%
		4000K	1410 lm ± 5%
		6000K	1435 lm ± 5%
	18W ± 10% (LD206 Round)	3000K	1415 lm ± 5%
		4000K	1465 lm ± 5%
		6000K	1515 lm ± 5%
	15W ± 10% (LD206 Square)	3000K	1220 lm ± 5%
		4000K	1390 lm ± 5%
		6000K	1410 lm ± 5%
	18W ± 10% (LD206 Square)	3000K	1385 lm ± 5%
		4000K	1445 lm ± 5%
		6000K	1520 lm ± 5%
Surface Color	White		